



**CA382 High-Temp Wet Tantalum Capacitor  
Tantalum Case for -55 +200 operation  
(hermetic seal)**

**1, Brief Introduction and Feature**

- 1) CA382, All tantalum case ,hermetic sealed, with high-temp insulated sleeve wet tantalum electrolytic capacitors.
- 2) With polar, axial leads through hole.High reliability,long life,
- 3) This unit have a 3V reverse voltage capability. Big ripple current.
- 4) Can use in high temperature area 200 available.
- 5) Widely used in electronic equipment for high-temp applications such as oil down hole drilling, aerospace,satellite,military equipment and other DC or PC.

Meet standard: Q/RTO.464.199-2014



**2, General Characteristics**

- 1) Operating Temperature: -55 +200 (>85 use voltage derating);
- 2) Storage temperature -62 +130
- 3) Capacitance Tolerance: K=±10% ,M=±20%,-10%~+30%, -20%~+50%
- 4) Leakage current: see the table 2 list
- 5) Ripple current: see the table 2 list
- 6) Dimensions and Max. weight: See table 1



**Table 1 Dimension**

Case Code	Dimension (mm)		L 1.5 (mm)	Max. Weight (g)
	Width	Length		

T2	7.14	7.92	16.3	7
T3	9.52	10.31	19.5	12
T4	9.52	10.31	27.0	18
*T5	9.52	10.31	27.8	20
*T6	9.9	10.7	27.2	22
*T7	9.9	10.7	30	24

Remark: \* means extend items.

Please read the important notes and cautions at the end of this document.

Document Number:150142 Revision:17-Apr.-15 <http://www.greentechie.com>

page 1

**GTCAP®**



**Hi-Temp Wet Tantalum Capacitor**  
**Shanghai Green Tech Co.,Ltd.**

CA382 series

3, Table 2 General characteristics

Rated Vol. (V)	A Derated Vol. 125 (V)	B Derated Vol. 200 (V)	Nominal Cap. (μF)	Dissipation Factor +25 +85 +200 (%)	Leakage current (μA)		Impedance 100Hz -55 ( )	Cap change rate (%)			85 40KHZ AC Ripple current (mA)	Case Code
					+25	+85 +125		-55	+85	+200		
6	4	3.6	30	7	1	2	100	-40	+11	+15	820	T1
			68	12			60		+14	+18	960	
			140	17		3	40		+20	+25	1200	T2
			270	30	2	7	25	-44	+18	+25	1375	
			330	30		8	20		+14	+20	1800	T3
			560	45		13	25		+18	+25	1900	
			1200	90	3	14	20	-80	+25	+30	2265	T4
8	5	4.8	25	7	1	2	100	-40	+11	+15	820	T1
			56	10			59		+14	+18	900	
			120	15			50		+20	+25	1220	T2
			220	30	2	7	30	-44	+18	+20	1370	
			290	30		6	25		+25	+25	1770	T3
			430	36		14	25		+25	+25	1825	
			850	50	4	16	22	-80	+25	+30	2330	T4
10	7	6	20	5	1	2	175	-32	+11	+15	820	T1
			47	11			100		+18	+15	855	
			100	12		4	60		+20	+20	1200	T2
			180	20	2	7	40	-36	+14	+20	1365	
			250	25		10	30		+25	+25	1720	T3
			390	25			25		+18	+25	1800	
			750	40	4		23	-80	+25	+30	2360	T4
15	10	9	15	5	1	2	155	-24	+11	+15	780	T1
			33	8			90		+14	+18	820	
			70	10		4	75		+18	+20	1150	T2
			120	15	2	7	50	-28	+18	+20	1450	
			170	20		10	35		+14	+20	1480	T3
			270	25		16	30		+18	+25	1740	
			540	35	6	20	23	-80	+25	+30	2330	T4
25	15	12	10	4	1	2	220	-16	+8	+10	715	T1
			22	5.5			140		+11		825	
			50	8			70		+13		1130	T2
			100	12	2	9	50	-28	+13		1435	
			120	18		6	38		+15	+15	1450	T3
			180	20		16	32		+25	+25	1525	
			350	30	7	21	24	-70	+25	+30	1970	T4

Please read the important notes and cautions at the end of this document.

Document Number:150142 Revision:17-Apr.-15 <http://www.greentechee.com>

page 2

GTCAP®



**Hi-Temp Wet Tantalum Capacitor**  
**Shanghai Green Tech Co.,Ltd.**

CA382 series

**Table 2 General characteristics**

Rated Vol. (V)	A Derated Vol. (V)	B Derated Vol. (V)	Nominal Cap. (μF)	Dissipation Factor +25 +85 +200 (%)	Leakage current (μA)		Impedance 100Hz -55 ( )	Cap change rate (%)		85 40KHZ AC Ripple current (mA)	Case Code	
					+25	+85 +125		-55	+85			
30	20	18	8	4	1	2	275	-16	+8	+12	640	T1
			15	5			175	-20	+11	+15	780	
			40	8		5	65	-24			1120	T2
			68	11		8	60		+13		1285	
			100	15	2	10	40	-28	+11	+18	1450	T3
			150	20		15	35	-48	+13	+25	1525	
			300	25	8	32	25	-60	+25	+35	1950	T4
50	30	30	5	3	1	2	400	-16	+5	+9	580	T1
			10	4		2	250	-24	+8	+12	715	
			25	7		5	95	-20	+11	+15	1005	T2
			47	10		8	70	-28	+13	+18	1155	
			60	10	2	10	45	-16	+11	+15	1335	T3
			82	12		12	45	-32	+13	+18	1400	
			160	15	8	30	27	-50	+25	+30	1900	T4
60	40	36	4	2.8	1	2	550	-16	+5	+9	525	T1
			8.2	4		2	275	-24	+8	+12	625	
			20	6		5	105	-16	+11	+15	930	T2
			39	8		8	90	-28			1110	
			50	9	2	10	50	-16			1330	T3
			68	10		10	45	-32			1365	
			140	12	8	30	28	-40	+20	+25	1850	T4
			*560	50	30	160	25	-60	+40	+50	2800	T5
75	50	45	3.5	2.5	1	2	650	-16	+5	+9	525	T1
			6.8	3.5		2	300	-20	+8	+12	610	
			15	5		5	150	-16			890	T2
			33	8	2	9	90	-24	+11	+15	1000	
			40	8		10	60	-16			1250	T3
			56	10		12		-28			1335	
100	65	60	110	10	9	30	29	-35	+20	+25	1850	T4
			2.5	2	1	2	950	-16	+7	+10	505	T1
			4.7	3		2	500	-20			565	
			11	5		4	200	-16	+8		835	T2
			22	6		9	100	-24			965	

Please read the important notes and cautions at the end of this document.

Document Number:150142 Revision:17-Apr.-15 <http://www.greentechie.com>

page 3

**GTCAP**®



**Hi-Temp Wet Tantalum Capacitor**  
**Shanghai Green Tech Co.,Ltd.**

**CA382 series**